

## MODELS | S4500 mono-S6000tri-S6500 mono

- Engine gasoline YANMAR
- Electric protection (IP23)
- Socket protection

Différentiel 30mA



MODEL		S4500	S6000 tri	S6500 mono
CODE		PD322SYA	PD572TYA	PD482SYA
EROGATION SYSTEMS		SINGLE PHASE	TRI PHASES	SINGLE PHASE
STARTING SYSTEM		ELECTRIC	ELECTRIC	ELECTRIC
TRIPHASES PHASE				
Power COP/LTP	kVA		5,62/6,86	
POWER LTP	kW		5,49	
Voltage	Volt		400	
Frequency	Hz		50	
Power factor	Cos φ		0,8	
SINGLE PHASE				
Power COP/LTP	kVA	3,45/4,05	3,30/4,53	4,84/5,90
POWER LTP	kW	3,65	4,07	5,31
Voltage	Volt	230	230	230
Frequency	Hz	50	50	50
Power factor	Cos φ	0,9	0,9	0,9
ENGINE				
Model		YANMAR L70	YANMAR L100	YANMAR L100
Displacement	cc	296	406	406
Number of cylinder		1 vertical	1 vertical	1 vertical
Power	kW	4,8	6,9	6,9
Fuel		gasoil	gasoil	gasoil
Aspiration		natural	natural	natural
TANK/AUTONOMY				
Tank capacity	L	3,5	5,5	5,5
Running time 3/4 load	h	3,4	3,9	3,9
NOISE LEVEL				
Noise level	dB(A)	///*	///*	///*
Noise level at 7m	dB(A)	///*	///*	///*
DIMENSIONS				
Lenght	mm	810	830	830
Width	mm	450	490	490
Height	mm	500	570	570
Weight	kg	84	112	105

TECHNICAL FEATURES

THE PRODUCER RESEVES THE RIGHT TO INTRODUCE CHANGES TO MODELS AND FEATURES WITHOUT PRIOR NOTICES - NON CONTRACTUAL PICTURES

LTP : Maximum Power      COP : Continuous Power

///\* Not compliant with directive 2000/14/EC